



## Features


- WQHD (2560 x 1440)
- Enhanced H.264
- Hacker Resistant
- Pre / Post Alarm Image
- Arm / Disarm Interface
- E2E Health Check
- Duplicated Recording

## Specifications

MODEL		GN6516	GN6608
CAMERA INTERFACE	CONFIGURATION	Shared Network	Dedicated Network
	RESOLUTIONS	WQHD, 1080P, 720P	
	MAX. CHANNELS	16	8
	DEDICATED VIDEO PORTS	-	8x, 100base-T, PoE
	COMPATIBLE MODELS	TeleEye MP400, MP200, MQ & ONVIF (Profile S)	
VIDEO	OUTPUTS	1 x HDMI, 1 x VGA (max. resolution 1080p)	
CODING	VIDEO & AUDIO	Enhanced H.264, H.264	
RECORDING	MODE	Manual, Scheduled, Event-driven	
	STORAGE	2 x SATA, internal	
	MAX. RECORDING PERFORMANCE	25fps per channel @ WQHD	
	DUPLICATED RECORDING	Yes	
EVENT	TYPES	External Alarm, Video Motion Detection, System Tamper, Power Interruption, HDD Failure	
	ACTIONS	Dial Back, Buzzer, Email Notification, Relay Control, Telemetry Preset	
	CONTROLS	Arm / Disarm, Security Switch, Power Interruption, System Tamper	
	ALARM INPUTS	4x on DVR or Alarm Inputs on Cameras	
	VIDEO MOTION DETECTION	Yes	
	PRE / POST ALARM IMAGE SEQUENCE	Yes	
AUDIO	INPUTS	1 x RCA on DVR or Audio Inputs on Cameras	
	OUTPUTS	1 x RCA on DVR or Audio Outputs on Cameras	
COMMUNICATION	NETWORK	100 / 1000 BASED-T	
	SURELINK	Yes	
	THROUGHPUT CONTROL	Yes	
	WEB SERVER	Built-in	
	JOYSTICK CONTROL	RX-KB05	
	USB	3 x USB 2.0	2 x USB 2.0
POWER	RATING	DC 12V, 4A	
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-10°C - 55°C	
	RELATIVE HUMIDITY	10% - 90%	
MECHANICAL DESIGN	DIMENSION	360mm x 242mm x 48mm	
	WEIGHT (kg)	1.8kg	2.0kg

## Dimensions

Unit: mm



www.TeleEye.com

## TeleEye Group

Hong Kong Bangladesh China Malaysia Philippines  
South Africa Sri Lanka Turkey U.K.

## DISTRIBUTED BY: