




## Features

- 1080p Dome
- 1/2.8" Sony 2MP Starlight CMOS sensor
- H.265 / Enhanced H.264 compression
- Vari-focal f=2.8mm ~ 12mm
- IP66 weather proof
- Vandal resistant
- Power over Ethernet
- ONVIF Profile S

## Dimension

Unit: mm



## Specifications

MODEL		MQ2211E-HD
VIDEO	IMAGE SENSOR	1/2.8" Sony 2MP Starlight CMOS
	RESOLUTION	1080p / 960p / 720p / XGA / D1
	FRAME RATE	Up to 30fps
	MINIMUM ILLUMINATION	Color: 0.01Lux / F1.4, B/W:0.005Lux / F1.4
	LENS	f=2.8mm ~12mm vari-focal lens
	VIEW ANGLE	35-97
	ELECTRONIC SHUTTER	Auto/ Manual (1/25~1/10000), FLK
	VIDEO SETTINGS	Brightness / Contrast / Saturation / Mirror / Exposure / Flickerless Control / Sharpness / TWDR / 3DNR
	ANALOG VIDEO OUTPUT	1CH 1.0Vp-p composite video output
AUDIO	INPUT	1CH Audio intercom input
	OUTPUT	1CH
CONNECTIVITY	NETWORK INTERFACE	RJ-45
	CONCURRENT USERS	4
	WEB SERVER	Built-in
	ONVIF	Profile S
COMPRESSION	VIDEO COMPRESSION	H.265 / Enhanced H.264
	VIDEO STREAMING	Dual-stream
EVENT HANDLING	PRIVACY ZONE	4
	SNAP SHOT	JPEG
	MOTION DETECTION	Yes
	ACTION	Recording, Alarm output, Email
	ALARM INPUT	2
	RELAY SWITCH	1
EDGE RECORDING	TF Card	Max. 64GB
POWER	VOLTAGE	12VDC
	MAX. RATING	7W
	POE	YES
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-20°C ~ 55°C
	RELATIVE HUMIDITY	0%-90%
MECHANICAL DESIGN	WEATHER PROOF	IP66
	VANDAL RESISTANT	IK10
	DIMENSION	117mm x 88.5mm
	WEIGHT	650g

**TeleEye Group**  
 Hong Kong China Malaysia Philippines  
 South Africa Sri Lanka Turkey U.K.

DISTRIBUTED BY:

[www.TeleEye.com](http://www.TeleEye.com)