





Features

- 1080p IR Bullet
- 1/2.8" Sony 2MP Starlight CMOS sensor
- H.265 / Enhanced H.264 compression
- Electric vari-focal
f=2.8mm ~ 8mm
- ~25m IR illumination range
- IP66 weather proof
- Power over Ethernet
- ONVIF Profile S

Dimension

Unit: mm



Specifications

MODEL		MQ2277E-HD
VIDEO	IMAGE SENSOR	1/2.8" Sony 2MP Starlight CMOS
	RESOLUTION	1080p / 960p / 720p / XGA / D1
	FRAME RATE	Up to 30fps
	MINIMUM ILLUMINATION	0Lux/F1.4 (IR ON) 15pcs IR LED ~25M, Color: 0.01Lux / F1.4, B/W: 0.005Lux / F1.4
	LENS	f=2.8mm ~ 8mm motorized lens (auto / manual focus)
	VIEW ANGLE	50-97
	ELECTRONIC SHUTTER	Auto/ Manual (1/25~1/10000), FLK
	VIDEO SETTINGS	Brightness / Contrast / Saturation / Mirror / Exposure / Flickerless Control / Sharpness / TWDR / 3DNR
	ANALOG VIDEO OUTPUT	1CH 1.0Vp-p composite video output
AUDIO	INPUT	1CH Audio intercom input
	OUTPUT	1CH
CONNECTIVITY	NETWORK INTERFACE	RJ-45
	CONCURRENT USERS	4
	WEB SERVER	Built-in
	ONVIF	Profile S
COMPRESSION	VIDEO COMPRESSION	H.265 / Enhanced H.264
	VIDEO STREAMING	Dual-stream
EVENT HANDLING	PRIVACY ZONE	4
	SNAP SHOT	JPEG
	MOTION DETECTION	Yes
	ACTION	Recording, Alarm output, Email
	ALARM INPUT	2
	RELAY SWITCH	1
EDGE RECORDING	TF Card	Max. 64GB
POWER	VOLTAGE	12VDC
	MAX. RATING	7W
	POE	YES
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-20°C ~ 55°C
	RELATIVE HUMIDITY	0%-90%
MECHANICAL DESIGN	WEATHER PROOF	IP66
	DIMENSION	117mm x 88mm x 81mm
	WEIGHT	700g

TeleEye Group
Hong Kong China Malaysia Philippines
South Africa Sri Lanka Turkey U.K.

DISTRIBUTED BY:

www.TeleEye.com