



PoE 10/100M x 16 + gigabit x 2 16-ch PoE Unmanaged Network Switch

Features

- IEEE 802.3af / 802.3at
- Fully compatible with WAMA IP-based products
- Plug-and-Play – zero configuration
- 123W for powering IP cameras
- 19" rack-mountable design

Specifications

Model	CO-16ES1
Pass Through Data Rates	16-Port 10/100Mbps; 2-Port 10/100/1000Mbps
PoE Standard	IEEE 802.3af, IEEE 802.3at (PoE+)
LED	Power (Green) 10/100 LNK / ACT (Green)
PoE Power Output	54V DC, 560mA, max. 30W per port, 123W (Total)
PoE Power Supply Type	1/2(+), 3/6(-), Mode-A, End-Span
Power Requirement	100~240V AC, 50-60Hz, 150W (Max.)
Storage Environment	-10°C ~ 55°C / 20 - 90% humidity (non-condensing)
Operating Environment	0°C ~ 40°C / 20 - 90% humidity (non-condensing)
Dimension (mm)	280 (W) x 180 (D) x 44 (H)
Weight	2 kg



WAMA Technology Limited

Unit 502, 5/F, Block B, Wing Kut Industrial Building,
608 Castle Peak Road, Kowloon, Hong Kong.

Tel : (852) 3703 9260

Email : info@wamatech.co

Fax : (852) 3705 0053

Website : www.wamatech.co