




Intelligent 4MP Vandal Resistant Dome IP Camera

Features

- 1/3" 4MP CMOS sensor
- H.265 / H.264 / M-JPEG dual streams
- Built-in video analytic functions
- Motorized vari-focal lens
- Micro SD slot for recording
- Day/Night (ICR), WDR, 3DNR, AGC
- ONVIF (Profile S)
- Power over Ethernet (PoE)



Dimensions



Specifications

Model	NF4-V56W
CAMERA	
Image Sensor	1/3" 4MP CMOS sensor
Effective Pixel	2592 (H) x 1520 (V)
Frame Rate	25/30fps
Resolution	Up to 2592 x 1520 (main stream); up to VGA (sub stream)
Video Compression	H.265, H.264, M-JPEG (16kbps – 8000kbps)
Audio Compression	G.711u (64kbps)
Open Standard	ONVIF (Profile S)
Min. Illumination	0.0 lux (IR on)
IR Range	25m
Sync System	Internal
Scan System	Progressive scan
Lens	2.8-12mm motorized lens
Angle of View	Horizontal: 32° ~ 86°; Vertical: 18° ~ 47°
Electronic Shutter	Auto / manual (1/30-1/10000) / FLK
CONTROL	
Video Adjustment	Brightness, contrast, saturation, sharpness, hue
3D Noise Reduction	Close / low / mid / mid-high / high
Digital WDR	Close / low / mid / high
Auto Gain Control	Low / mid-low / mid / mid-high / high
Day / Night	Auto / color / B/W / external
Privacy Mask	4 zones
Mirror	Close / horizontal / vertical / 90° rotation / 180° rotation / 270° rotation
Slow Shutter	Close / open
EVENT	
Event Type	External alarm, video motion detection, video tamper, network interruption
Video Analysis	Tripwire, loitering, missing / unattended object detection, crowd monitoring
Action Type	Dial-back, snapshot, relay switch control, email notification, micro SD card recording
External Alarm Input	2
Motion Detection	4
Relay Output	1
COMMUNICATION	
Network	RJ-45, 100 base-T
Protocol	TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, SMTP(SSL), PPPoE, UPNP, NTP, P2P, FTP
Concurrent Connection	4
Audio Input	1
Audio Output	1
Video Output	1 (CVBS)
MISCELLANEOUS	
Environmental Protection	IP67, IK10
Operating Environment	-20 ~ 55°C / 90% relative humidity (no condensation)
Power Supply	DC12V / PoE, 8W
Dimensions (mm)	123 (H) x Φ132 (D)
Weight	830g
Accessories	CC-WL0V5, CC-DP0V5

