





Starlight Intelligent 2MP Bullet IP Camera

Features

- Sony 1/2.8" 2.1MP STARVIS sensor
- Starlight sensitivity
- H.265 / H.264 / M-JPEG dual streams
- Built-in video analytic functions
- Motorized vari-focal lens
- Micro SD slot for recording
- Day/Night (ICR), T-WDR (120dB), 3DNR, AGC, defogging
- ONVIF (Profile S)
- Power over Ethernet (PoE)



Dimensions



Specifications

| Model | NV2-B36W |
|-----------------------|--|
| CAMERA | |
| Image Sensor | Sony 1/2.8" 2.1MP STARVIS sensor |
| Effective Pixel | 1920 (H) x 1080 (V) |
| Frame Rate | 25/30fps |
| Resolution | Up to 1080p (main stream); up to D1 (sub stream) |
| Video Compression | H.265, H.264, M-JPEG (16kbps – 8000kbps) |
| Audio Compression | G.711A (64kbps) |
| Open Standard | ONVIF (Profile S) |
| Min. Illumination | 0.0 lux (IR on), 0.002 lux@F1.4 (IR off) |
| IR Range | 40m |
| Sync System | Internal |
| Scan System | Progressive scan |
| Lens | 2.8-12mm motorized lens |
| Angle of View | Horizontal: 34° ~ 97°; Vertical: 19° ~ 51° |
| Electronic Shutter | Auto / manual (1/30-1/10000) / FLK |
| S/N Ratio | ≥50db |
| CONTROL | |
| Video Adjustment | Brightness, contrast, saturation, sharpness, hue |
| 3D Noise Reduction | Close / low / mid / mid-high / high |
| True WDR | Close / low / mid / high |
| Auto Gain Control | Low / mid-low / mid / mid-high / high |
| Day / Night | Auto / color / B/W / external |
| Privacy Mask | 4 zones |
| Mirror | Close / horizontal / vertical / 90° rotation / 180° rotation / 270° rotation |
| Defogging | Close / low / mid / high |
| Slow Shutter | Close / open |
| EVENT | |
| Event Type | External alarm, video motion detection, video tamper, network interruption |
| Video Analysis | Tripwire, loitering, missing / unattended object detection, crowd monitoring |
| Action Type | Dial-back, snapshot, relay switch control, email notification, micro SD card recording |
| External Alarm Input | 2 |
| Motion Detection | 4 |
| Relay Output | 1 |
| COMMUNICATION | |
| Network | RJ-45, 100 base-T |
| Protocol | TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, SMTP(SSL), PPPoE, UPNP, NTP, P2P, FTP |
| Concurrent Connection | 4 |
| Audio Input | 1 |
| Audio Output | 1 |
| Video Output | 1 (CVBS) |
| MISCELLANEOUS | |
| Weather Protection | IP66 |
| Operating Environment | -20 ~ 55°C / 90% relative humidity (no condensation) |
| Power Supply | DC12V / PoE, 10W |
| Dimensions (mm) | 93 (W) x 96 (H) x 263 (L) |
| Weight | 904g |



WAMA Technology Limited

Unit 502, 5/F, Block B, Wing Kut Industrial Building,
608 Castle Peak Road, Kowloon, Hong Kong.

Tel : (852) 3703 9260

Email : info@wamatech.co

Fax : (852) 3705 0053

Website : www.wamatech.co